



司騰達股份有限公司  
BHP Industry Solution



EtherNet/IP


CC-Link



CANopen



Now with ...  
CPC UA



DeviceNet



# 司騰達股份有限公司

HMS 台灣總代理 – Remote Access 跨國遠端連線與自動化工業的最佳選擇

司騰達公司致力於推廣數位化工廠和 IIoT 工業物聯網的解決方案，並與歐洲最先進的公司 – HMS 集團合作，同時透過引進更多歐美的技術能量，提供客戶關於工業 4.0 的顧問諮詢服務，並將教育與產業連結，協助台灣產業逐步完成從現場設備、生產資訊、通訊 IoT 的垂直整合，並整合 M2M 工業總線與軟體開發，從而實現數位化工廠與自動化機械領域的創新。

LINE



官網



司騰達聯絡訊息

臺北客服專線：(02)-2242-1625

台中客服專線：(04)-2451-0611

客服信箱：sales@bhp.com.tw

Line ID：@bhp.tw

www.bhp.com.tw



## Infrastructure product

### Anybus PoE Injector 12-57VDC

The Anybus Power over Ethernet Injector (PoE) makes it possible to supply an Anybus product, for example an Anybus WLAN Access point or Anybus Wireless Bolt RJ45, with power through an Ethernet cable. This removes the need for an additional power cable.



This industrial-grade 2-port Gigabit High Power injector version has high reliability and a rigid IP30 metal enclosure.

#### FEATURES & BENEFITS

- Industrial 2-port Gigabit High Power PoE Injector
- Supports 2x10/100/1000Base-T(X) for power and data Output
- Fully compliant with IEEE802.3at/802.3af standard
- Auto protection for Over Voltage Power Input and over current output
- Supports Power Output up to 30 Watts per port
- High reliability and rigid IP30 housing
- DIN-Rail and Wall Mount Design

#### TECHNICAL SPECIFICATIONS

<b>Wired interface</b>	2x RJ45 Ethernet Port Input (Data, 10/100/1000 Base-T(x)) 2x RJ45 Ethernet Port with P.S.E. Output (Data and power, 10/100/1000 Base-T(x))
<b>POE standard</b>	IEEE 802.11 af/at
<b>Dimensions (WxHxD)</b>	41 x 95 x 70 mm
<b>Weight</b>	370 g
<b>Operating temperature</b>	-20 to +70 °C or -4 to +158 °F (Storage temp: -40 to +80 °C or -40 to +176 °F )
<b>Input voltage</b>	12-57 VDC on 4-pin screw terminal block
<b>Output voltage</b>	50V / 600mA, 30 Watts max. Per port
<b>LED Power indicator</b>	PWR / Ready: 1 x LED Green On: Power is on and functioning normally.
<b>LED PoE Indicators</b>	2 x LED Blue On: PoE Device Link

	Blue Blinking: Detecting PoE Device Blue Off : None PoE Device Detected
<b>Power protection</b>	Short Circuit, Overload & High Voltage protection
<b>Enclosure material</b>	Metal
<b>Mechanical rating</b>	IP30
<b>Mounting</b>	DIN-rail + Wall-mount (included)
<b>Certification</b>	CE-marked
<b>CERTIFICATIONS</b>	
<b>UL</b>	UL 61010-2-201 / UL file E214107
<b>EMI</b>	FCC Part 15, EN55022 class B
<b>EMS</b>	EN61000-4-2 (ESD), EN61000-4-3 (RS), EN61000-4-4 (EFT), EN61000-4-5 (Surge), EN61000-4-6 (CS), EN61000-4-8, EN61000-4-11
<b>Safety</b>	EN60950-1
<b>Shock</b>	IEC60068-2-27
<b>Free Fall</b>	IEC60068-2-32
<b>Vibration</b>	IEC60068-2-6

File	Version	Size	Read online
------	---------	------	-------------

## Content of delivery

1x Anybus PoE Injector  
DIN-Rail mount kit  
Wall mount kit  
Installation guide

## Ordering Information

<b>Order code</b>	AWB4006
-------------------	---------

3 year guarantee.

# 司騰達股份有限公司

自動化工業與跨國遠端連線的最佳選擇

Ewon Flexy205

VPN+IOT 物聯網模組

Ewon Cosy131


VPN 遠端連線



Anybus X-Gateway



CODESYS SoftPLC



Jmobile HMI/SCADA IPC



## 工業 4.0 數位工廠與 工業物聯網解決方案

i4-SCADA IPC



WAGO750 RemoteIO

EtherCAT  
PROFINET



SIEMENS ET 200SP  
PROFINET Remote Io



SDP 系列  
EtherCAT 伺服馬達



eSMART Web HMI  
Esmart04/07/10

## 司騰達股份有限公司

台北營業所：235602 新北市中和區中山路 2 段 299 號 5 樓之 1

Tel：(02)-2242-1625 Fax：(02)-2242-1605

台中營業所：40760 台中市西屯區廣福路 186 號

Tel：(04)-2451-0611 Fax：(04)-2451-0612

E-mail：sales@bhp.com.tw

Line ID：@bhp.tw



司騰達股份有限公司  
BHP Industry Solution

LINE



官網



了解更多產品詳細資訊請上官網查詢  
www.bhp.com.tw