



司騰達股份有限公司
BHP Industry Solution



EtherNet/IP

CC-Link



CANopen



DeviceNet



司騰達股份有限公司

HMS 台灣總代理 — Remote Access 跨國遠端連線與自動化工業的最佳選擇

司騰達公司致力於推廣數位化工廠和IIoT工業物聯網的解決方案，並與歐洲最先進的公司—HMS集團合作，同時透過引進更多歐美的技術能量，提供客戶關於工業4.0的顧問諮詢服務，並將教育與產業連結，協助台灣產業逐步完成從現場設備、生產資訊、通訊IoT的垂直整合，並整合M2M工業總線與軟體開發，從而實現數位化工廠與自動化機械領域的創新。

LINE



官網



司騰達聯絡訊息

臺北客服專線：(02)-2242-1625

台中客服專線：(04)-2451-0611


客服信箱：sales@bhp.com.tw

Line ID：@bhp.tw

www.bhp.com.tw

P6157

15.6" WXGA TFT Widescreen Industrial LCD Monitor



1. USB touch interface
2. Audio (Line-in)
3. VGA
4. HDMI
5. DisplayPort

Features

- 15.6" WXGA TFT with 400 nits of brightness
- Projective capacitive multi-touch
- NEMA 4/12 (IP65) compliant flat panel monitor
- Supports panel mount, wall mount, and VESA mount
- Full-range, screw-type (locked) AC input or 24VDC input (optional)
- Multi-signal inputs: HDMI, DisplayPort, and VGA



- ▲ Ultra-slim mechanism design

Introduction

The P6157W-V3 is a slim-type industrial LCD monitor with a flat front bezel design. It features a 15.6-inch, 400-nit WXGA LCD display and supports multiple signal interfaces, including DisplayPort, VGA, and HDMI. The monitor's IP65 (NEMA 4)-rated front bezel, screw-type adapter plug design, and 12/24V DC input make it suitable for a wide range of industrial environments. Additionally, the P6157W-V3 supports panel mount, wall mount, or VESA FPM PMI (Video Electronics Standards Association Flat Panel Monitor Physical Mounting Interface) mounting. Its compact design allows for easy deployment in space-limited areas, making it particularly suitable for POI/POS systems, HMI applications, and various heavy-duty industrial fields.

Specifications

Front Bezel	NEMA 4/12 (IP65)-compliant and flat front bezel	
Mounting	Panel mount, wall mount, and VESA arm FPM PMI mounting (video electronics standards association Flat Panel monitor physical mounting interface)	
LCD Panel	Display	15.6" WXGA TFT LCD
	Max. Resolution	1366 x 768
	Max. Colors	16.7M
	Active Area (mm)	344.232 x 193.536
	Pixel Pitch (mm)	0.252 x 0.252
	Response Time	8ms
	Backlight	LED
	Backlight MTBF	50,000 hrs
	Viewing Angle (H/V)	170°/160°
	Contrast Ratio	500 (TYP.)
Brightness (cd/m ²)	400 nits	

Display Control	OSD (on screen display)
Input Signal	VGA HDMI DisplayPort Touchscreen: USB interface
I/O Connectors	1 x USB for touchscreen version 1 x Audio (Line-in) 1 x VGA 1 x DisplayPort 1 x HDMI 1 x Power input with screw type connector (AC version) 1 x Power input with terminal block (DC version)
Audio	2 x Speaker
Power Supply	AC version: 100 to 240 VAC-DC, 12V3A, 36W power adapter DC version: 24 VDC
Power Consumption	17W
Touchscreen	Projective capacitive multi-touch
Dimensions	396.8 mm (15.62") (W) x 54 mm (2.13") (D) x 247.1 mm (9.73") (H)
Packing Dimensions	535 mm (21.06") (W) x 196 mm (7.71") (D) x 485 mm (19.09") (H)
Weight (net/gross)	4.1 kg (9.1 lb)/6.1 kg (13.44 lb)
Operating temperature	-10°C to +50°C (+14°F to +122°F)
Relative humidity	10% to 90% @ +40°C, non-condensing
Certifications	CE, EN 61000-6-2, EN 61000-6-4, and FCC Class A

Ordering Information

P6157W-V3

P6157-BHP-A1	P6157WPC-AC 15.6" industrial monitor with capacitive touch screen and AC version
--------------	--

* Other configuration by request

* Specification and certifications may vary based on different requirements


Packing List

1 x P6157W-V3 unit
1 x VGA cable
1 x USB cable for touch
1 x Audio cable
1 x Adapter (AC version only)
1 x 3-pin Terminal block (DC version only)

Optional Accessories

509000001500	Adaptor 24V/120W,wire only
599000001100	US 1.8M power cord
59904010000E	UK 1.83M power cord
59903000000E	EU 1.83M power cord
590000012700	HDMI cable
590000020900	DisplayPort cable 2M
E29R131102	Panel mount kit
E29R131114	Wall mount kit
E221177116	Desktop stand for 15.6" to 21.5"

Dimensions



司騰達股份有限公司

自動化工業與跨國遠端連線的最佳選擇

Ewon Flexy205

VPN+IOT 物聯網模組


Ewon Cosy
VPN 遠端連線



Anybus X-Gateway



CODESYS SoftPLC



Jmobile HMI/SCADA IPC



工業 4.0 數位工廠與 工業物聯網解決方案

i4-SCADA IPC



WAGO750 Remote IO
EtherCAT / PROFINET



SIEMENS ET 200SP
PROFINET Remote IO



MR JET 系列
EtherCAT 伺服馬達



eSMART Web HMI
Esmart04/07/10

司騰達股份有限公司

台北營業所：235602 新北市中和區中山路 2 段 299 號 5 樓之 1

Tel : (02)-2242-1625 Fax : (02)-2242-1605

台中營業所：40760 台中市西屯區廣福路 186 號

Tel : (04)-2451-0611 Fax : (04)-2451-0612

E-mail : sales@bhp.com.tw

Line ID : @bhp.tw



司騰達股份有限公司
BHP Industry Solution

LINE



官網



了解更多產品詳細資訊請上官網查詢
www.bhp.com.tw